## § 265.14

- (i) The sampling of impoundment contents:
  - (ii) The analysis of test data; and,
- (iii) The annual removal of residues which are not delisted under §260.22 of this chapter or which exhibit a characteristic of hazardous waste and either:
- (A) Do not meet applicable treatment standards of part 268, subpart D; or
- (B) Where no treatment standards have been established;
- (1) Such residues are prohibited from land disposal under §268.32 or RCRA section 3004(d); or
- (2) Such residues are prohibited from land disposal under §268.33(f).
- (8) For owners and operators seeking an exemption to the air emission standards of Subpart CC of this part in accordance with § 265.1083—
- (i) If direct measurement is used for the waste determination, the procedures and schedules for waste sampling and analysis, and the results of the analysis of test data to verify the exemption.
- (ii) If knowledge of the waste is used for the waste determination, any information prepared by the facility owner or operator or by the generator of the hazardous waste, if the waste is received from off-site, that is used as the basis for knowledge of the waste.
- (c) For off-site facilities, the waste analysis plan required in paragraph (b) of this section must also specify the procedures which will be used to inspect and, if necessary, analyze each movement of hazardous waste received at the facility to ensure that it matches the identity of the waste designated on the accompanying manifest or shipping paper. At a minimum, the plan must describe:
- (1) The procedures which will be used to determine the identity of each movement of waste managed at the facility; and
- (2) The sampling method which will be used to obtain a representative sample of the waste to be identified, if the identification method includes sampling.
- (3) The procedures that the owner or operator of an off-site landfill receiving containerized hazardous waste will use to determine whether a hazardous waste generator or treater has added a

biodegradable sorbent to the waste in the container.

[45 FR 33232, May 19, 1980, as amended at 50 FR 4514, Jan. 31, 1985; 50 FR 18374, Apr. 30, 1985; 51 FR 40638, Nov. 7, 1986; 52 FR 25788, July 8, 1987; 54 FR 33396, Aug. 14, 1989; 55 FR 25685, June 1, 1990; 55 FR 25506, June 21, 1990; 56 FR 19290, Apr. 26, 1991; 57 FR 8088, Mar. 6, 1992; 57 FR 54461, Nov. 18, 1992; 59 FR 62935, Dec. 6, 1994; 61 FR 4913, Feb. 9, 1996]

## §265.14 Security.

- (a) The owner or operator must prevent the unknowing entry, and minimize the possibility for the unauthorized entry, of persons or livestock onto the active portion of his facility, wales:
- (1) Physical contact with the waste, structures, or equipment with the active portion of the facility will not injure unknowing or unauthorized persons or livestock which may enter the active portion of a facility, and
- (2) Disturbance of the waste or equipment, by the unknowing or unauthorized entry of persons or livestock onto the active portion of a facility, will not cause a violation of the requirements of this part.
- (b) Unless exempt under paragraphs (a)(1) and (2) of this section, a facility must have:
- (1) A 24-hour surveillance system (e.g., television monitoring or surveillance by guards or facility personnel) which continuously monitors and controls entry onto the active portion of the facility: or
- (2)(i) An artificial or natural barrier (e.g., a fence in good repair or a fence combined with a cliff), which completely surrounds the active portion of the facility; and
- (ii) A means to control entry, at all times, through the gates or other entrances to the active portion of the facility (e.g., an attendant, television monitors, locked entrance, or controlled roadway access to the facility).

[Comment: The requirements of paragraph (b) of this section are satisfied if the facility or plant within which the active portion is located itself has a surveillance system, or a barrier and a means to control entry, which complies with the requirements of paragraph (b)(1) or (2) of this section.]

(c) Unless exempt under paragraphs (a)(1) and (a)(2) of this section, a sign

with the legend, "Danger-Unauthorized Personnel Keep Out," must be posted at each entrance to the active portion of a facility, and at other locations, in sufficient numbers to be seen from any approach to this active portion. The legend must be written in English and in any other language predominant in the area surrounding the facility (e.g., facilities in counties bordering the Canadian province of Quebec must post signs in French; facilities in counties bordering Mexico must post signs in Spanish), and must be legible from a distance of at least 25 feet. Existing signs with a legend other than "Danger—Unauthorized Personnel Keep Out" may be used if the legend on the sign indicates that only authorized personnel are allowed to enter the active portion, and that entry onto the active portion can be dangerous.

[Comment: See §265.117(b) for discussion of security requirements at disposal facilities during the post-closure care period.]

[45 FR 33232, May 19, 1980, as amended at 71 FR 40274, July 14, 2006]

## § 265.15 General inspection requirements.

(a) The owner or operator must inspect his facility for malfunctions and deterioration, operator errors, and discharges which may be causing—or may lead to: (1) Release of hazardous waste constituents to the environment or (2) a threat to human health. The owner or operator must conduct these inspections often enough to identify problems in time to correct them before they harm human health or the environment.

(b)(1) The owner or operator must develop and follow a written schedule for inspecting all monitoring equipment, safety and emergency equipment, security devices, and operating and structural equipment (such as dikes and sump pumps) that are important to preventing, detecting, or responding to environmental or human health hazards.

- (2) He must keep this schedule at the facility.
- (3) The schedule must identify the types of problems (e.g., malfunctions or deterioration) which are to be looked for during the inspection (e.g., inoper-

ative sump pump, leaking fitting, eroding dike, etc.).

- (4) The frequency of inspection may vary for the items on the schedule. However, the frequency should be based on the rate of deterioration of the equipment and the probability of an environmental or human health incident if the deterioration, malfunction, or operator error goes undetected between inspections. Areas subject to spills, such as loading and unloading areas, must be inspected daily when in use, except for Performance Track member facilities, that must inspect at least once each month, upon approval by the Director, as described in paragraph (b)(5) of this section. At a minimum, the inspection schedule must include the items and frequencies called for in §§ 265.174, 265.193, 265.195, 265.226, 265.260, 265.278, 265.304, 265.347, 265.377, 265.403, 265.1033, 265.1052,265.1053, 265.1058, and 265.1084 through 265.1090, where applicable.
- (5) Performance Track member facilities that choose to reduce inspection frequencies must:
- (i) Submit an application to the Director. The application must identify the facility as a member of the National Environmental Performance Track Program and identify the management units for reduced inspections and the proposed frequency of inspections. Inspections must be conducted at least once each month.
- (ii) Within 60 days, the Director will notify the Performance Track member facility, in writing, if the application is approved, denied, or if an extension to the 60-day deadline is needed. This notice must be placed in the facility's operating record. The Performance Track member facility should consider the application approved if the Director does not: (1) Deny the application; or (2) notify the Performance Track member facility of an extension to the 60day deadline. In these situations, the Performance Track member facility must adhere to the revised inspection schedule outlined in its application and maintain a copy of the application in the facility's operating record.
- (iii) Any Performance Track member facility that discontinues its membership or is terminated from the program must immediately notify the Director